

MEGA EQUIPMENT CO.

GENERATORS FOR SALE

SN	Image	Model	Power (in KW)	Price (\$USD)	Specification																																							
1.		2011 OLYMPIAN GEH220	180 KW	\$39,900	<table><tr><th colspan="2">Technical Data</th></tr><tr><td>Engine Make & Model:</td><td>Perkins™ 1106A-70TAG4</td></tr><tr><td>Alternator Model:</td><td>LL5014F</td></tr><tr><td>Control Panel:</td><td>PowerWizard 1.1</td></tr><tr><td>Base Frame Type:</td><td>Heavy Duty Fabricated Steel</td></tr><tr><td>Circuit Breaker Type:</td><td>3 Pole MCCB</td></tr></table>	Technical Data		Engine Make & Model:	Perkins™ 1106A-70TAG4	Alternator Model:	LL5014F	Control Panel:	PowerWizard 1.1	Base Frame Type:	Heavy Duty Fabricated Steel	Circuit Breaker Type:	3 Pole MCCB																											
Technical Data																																												
Engine Make & Model:	Perkins™ 1106A-70TAG4																																											
Alternator Model:	LL5014F																																											
Control Panel:	PowerWizard 1.1																																											
Base Frame Type:	Heavy Duty Fabricated Steel																																											
Circuit Breaker Type:	3 Pole MCCB																																											
2.		2012 FG WILSON 250H2	200 KW	\$24,900	<table><tr><th colspan="3">Ratings and Performance Data</th></tr><tr><td>Engine Make & Model:</td><td colspan="2">Perkins® 1306A-E87TAG4</td></tr><tr><td>Alternator manufactured for FG Wilson by:</td><td colspan="2">Leroy Somer</td></tr><tr><td>Alternator Model:</td><td colspan="2">LL5014H</td></tr><tr><td>Control Panel:</td><td colspan="2">PowerWizard 1.1</td></tr><tr><td>Base Frame:</td><td colspan="2">Heavy Duty Fabricated Steel</td></tr><tr><td>Circuit Breaker Type:</td><td colspan="2">3 Pole MCCB</td></tr><tr><td>Frequency:</td><td>50 Hz</td><td>60 Hz</td></tr><tr><td>Engine Speed: RPM</td><td>1500</td><td>1800</td></tr><tr><td>Fuel Tank Capacity: litres (US gal)</td><td colspan="2">350 (92.5)</td></tr><tr><td>Fuel Consumption: l/hr (US gal/hr)</td><td colspan="2"></td></tr><tr><td>(100% Load)</td><td>- Prime</td><td>50.0 (13.2) 54.9 (14.5)</td></tr><tr><td></td><td>- Standby</td><td>53.9 (14.2) 58.2 (15.4)</td></tr></table>	Ratings and Performance Data			Engine Make & Model:	Perkins® 1306A-E87TAG4		Alternator manufactured for FG Wilson by:	Leroy Somer		Alternator Model:	LL5014H		Control Panel:	PowerWizard 1.1		Base Frame:	Heavy Duty Fabricated Steel		Circuit Breaker Type:	3 Pole MCCB		Frequency:	50 Hz	60 Hz	Engine Speed: RPM	1500	1800	Fuel Tank Capacity: litres (US gal)	350 (92.5)		Fuel Consumption: l/hr (US gal/hr)			(100% Load)	- Prime	50.0 (13.2) 54.9 (14.5)		- Standby	53.9 (14.2) 58.2 (15.4)
Ratings and Performance Data																																												
Engine Make & Model:	Perkins® 1306A-E87TAG4																																											
Alternator manufactured for FG Wilson by:	Leroy Somer																																											
Alternator Model:	LL5014H																																											
Control Panel:	PowerWizard 1.1																																											
Base Frame:	Heavy Duty Fabricated Steel																																											
Circuit Breaker Type:	3 Pole MCCB																																											
Frequency:	50 Hz	60 Hz																																										
Engine Speed: RPM	1500	1800																																										
Fuel Tank Capacity: litres (US gal)	350 (92.5)																																											
Fuel Consumption: l/hr (US gal/hr)																																												
(100% Load)	- Prime	50.0 (13.2) 54.9 (14.5)																																										
	- Standby	53.9 (14.2) 58.2 (15.4)																																										
3.		CATERPILLAR 3406	300 KW	\$39,900	<p>SUMMARY PRODUCT INFORMATION THIS PRODUCT INFORMATION IS NOT A FULL SPECIFICATION, SOME PARAMETERS MAY VARY.</p> <table><tr><td>Maximum Electrical Output (Prime Power @ 0.8 pf)</td><td>365 kVA / 292 kW</td></tr><tr><td>Maximum Load</td><td>507 Amps</td></tr><tr><td>Nominal Output Voltage – Phase to Phase</td><td>415 Volts (+/-10 %)</td></tr><tr><td>Nominal Frequency</td><td>50 (Hz)</td></tr><tr><td>Maximum Ambient Temperature</td><td>50°C</td></tr><tr><td>Maximum Sound Level</td><td>85db(A) at 1 mtr</td></tr><tr><td>Overall Length</td><td>5000 mm</td></tr><tr><td>Overall Width</td><td>2000 mm</td></tr><tr><td>Overall Height (Inc exhaust / lifting lugs)</td><td>2600 mm</td></tr></table>	Maximum Electrical Output (Prime Power @ 0.8 pf)	365 kVA / 292 kW	Maximum Load	507 Amps	Nominal Output Voltage – Phase to Phase	415 Volts (+/-10 %)	Nominal Frequency	50 (Hz)	Maximum Ambient Temperature	50°C	Maximum Sound Level	85db(A) at 1 mtr	Overall Length	5000 mm	Overall Width	2000 mm	Overall Height (Inc exhaust / lifting lugs)	2600 mm																					
Maximum Electrical Output (Prime Power @ 0.8 pf)	365 kVA / 292 kW																																											
Maximum Load	507 Amps																																											
Nominal Output Voltage – Phase to Phase	415 Volts (+/-10 %)																																											
Nominal Frequency	50 (Hz)																																											
Maximum Ambient Temperature	50°C																																											
Maximum Sound Level	85db(A) at 1 mtr																																											
Overall Length	5000 mm																																											
Overall Width	2000 mm																																											
Overall Height (Inc exhaust / lifting lugs)	2600 mm																																											
4.		CATERPILLAR 3406	300 KW	\$40,000	<p>SUMMARY PRODUCT INFORMATION THIS PRODUCT INFORMATION IS NOT A FULL SPECIFICATION, SOME PARAMETERS MAY VARY.</p> <table><tr><td>Maximum Electrical Output (Prime Power @ 0.8 pf)</td><td>365 kVA / 292 kW</td></tr><tr><td>Maximum Load</td><td>507 Amps</td></tr><tr><td>Nominal Output Voltage – Phase to Phase</td><td>415 Volts (+/-10 %)</td></tr><tr><td>Nominal Frequency</td><td>50 (Hz)</td></tr><tr><td>Maximum Ambient Temperature</td><td>50°C</td></tr><tr><td>Maximum Sound Level</td><td>85db(A) at 1 mtr</td></tr><tr><td>Overall Length</td><td>5000 mm</td></tr><tr><td>Overall Width</td><td>2000 mm</td></tr><tr><td>Overall Height (Inc exhaust / lifting lugs)</td><td>2600 mm</td></tr></table>	Maximum Electrical Output (Prime Power @ 0.8 pf)	365 kVA / 292 kW	Maximum Load	507 Amps	Nominal Output Voltage – Phase to Phase	415 Volts (+/-10 %)	Nominal Frequency	50 (Hz)	Maximum Ambient Temperature	50°C	Maximum Sound Level	85db(A) at 1 mtr	Overall Length	5000 mm	Overall Width	2000 mm	Overall Height (Inc exhaust / lifting lugs)	2600 mm																					
Maximum Electrical Output (Prime Power @ 0.8 pf)	365 kVA / 292 kW																																											
Maximum Load	507 Amps																																											
Nominal Output Voltage – Phase to Phase	415 Volts (+/-10 %)																																											
Nominal Frequency	50 (Hz)																																											
Maximum Ambient Temperature	50°C																																											
Maximum Sound Level	85db(A) at 1 mtr																																											
Overall Length	5000 mm																																											
Overall Width	2000 mm																																											
Overall Height (Inc exhaust / lifting lugs)	2600 mm																																											

If you are interested in any of the above products or would like to discuss more about any specific products or details, please feel free to get in touch with us.

Phone: 647 804 7553 | Email: sales@megaequipment.ca | Website: www.megaequipment.ca